



# Epson Series UV Roll to Roll Printer

UV卷材打印机 — 高性价比之选

Dual Heads

双喷头

4/ 5/ 6-Color

4/ 5/ 6色写真

White & Fluorescent Color Optional

白色&荧光色可选

Variable Dot

可变墨滴

Epson Official Supplied i1600-U Printheads

配备爱普生官方原装i1600-U喷头



**PRECISIONCORE**  
PRINTHEAD  
powered by EPSON

# UV Roll to Roll Printer | UV-740D

## ● Features




### Epson PrecisionCore Technology

Equipped Epson i1600-U Head.  
4 colors and 5 colors models are optional



### High Quality Component

Branded accessories are used for high attrition areas. Greatly increased the lifetime and stability of the machine. For example, the Hiwin guide rail, German Igus drag chain, Italian Megadyne belt.



### Variable Dot Print Technology

Permitting the printer to provide smooth gradations, exceptional solid colors and optimum image quality in all print modes



### Anti-Collision Function

Anti-collision system is equipped to protect the printhead and carriage all the time



### Adjustable Pinch Roller

Adjustable three gear pressure for pinch roller. Guarantee the evenly force to full width of the material, ensure the high precision media stepping

- ★ High-density UV curable ink produces rich, vibrant colors on coated or uncoated media.
- ★ Durable, scratch-resistant and virtually odorless, Up to three years outdoor durability without lamination.
- ★ Big functional control panel adopts the latest program Intelligent error auto-detection boards, it can guide user to find solution very quickly.



## ● Specification

Model No.	<b>UV-740D</b>	
Printing Head	2 × Epson i1600-U	
Resolution	2400 dpi MAX	
Media	Width	1800 mm MAX
	Type	Canvas, Leather, PET Film, Reflective Film, Soft Ceiling Film Etc.
Ink	Type	UV Ink
	Color	CMYK / CMYK+W
	Curing	High Quality Water Cooling UV-LED Lamp
Speed	Printing Mode	CMYK
	Draft	45 m <sup>2</sup> /h
	Production	24 m <sup>2</sup> /h
	Quality	12 m <sup>2</sup> /h
Cleaning	Automatic Cleaning, Anti-Clogging Flash Function & Capping System	
Feed & TakeUp	Automatic Media Feeding (Standard) & Take up System (Optional)	
Rip Software	Maintop (Standard) / FlexiPRINT (Optional)	
Connector	USB 3.0	
Power	AC 110/ 220V, 50/ 60Hz, 1600W	
Size	Machine	L3130×W710×H1380 mm
	Packing	L3210×W1000×H740 mm
Weight	Machine	280 KG
	Packing	400 KG

Specifications are subject to change without notice.