

# Eco Solvent Printer

1.8m i3200 Printhead

1.8米 爱普生 i3200 户内外写真机

- |                |      |
|----------------|------|
| Dual Heads     | 双喷头  |
| 4 Color        | 4色写真 |
| Variable Dot   | 可变墨滴 |
| 3-Stage Heater | 三段加热 |




# Eco Solvent Printer | SJ-740S & SJ-740i

## ● Features



### Epson PrecisionCore Printheads

Equipped with Epson i3200-E printhead, powered by Epson PrecisionCore technology. Born for fast speed and long-term running.



### Heating And Drying System

Front and middle and rear heating system and front drying fan are standard equipped to help dry the printed material fast.




### Anti-Collision Function

Anti-collision system is equipped to protect the printhead and carriage all the time.



### Branded Parts

Greatly increased the lifetime and stability of the machine. For example, Hiwin guide rail, German Igus drag chain, Italian Megadyne belt.



### Variable Dot Print Technology

Permitting the printer to provide smooth gradations, exceptional solid colors and optimum image quality in all print modes.

- ★ New look has heavier, larger structure, and wider printing platform
- ★ Aluminous carriage girder ensures high accuracy of carriage movement
- ★ Dual feeding bar for loading heavy media
- ★ Optional infrared heater for drying prints quickly
- ★ Integrated temperature controller



## ● Specification

Model No.		<b>SJ-740S</b>	<b>SJ-740i</b>
Printhead		2×Epson i3200	1×Epson i3200
Resolution		2400dpi max	2400dpi max
Ink Color		CMYK	CMYK
Media	Size	1.8 meter	
	Types	Flex Banner , Vinyl, One Way Vision, Banner Cloth, Window Film, Mesh Etc.	
Speed	Draft	42 m <sup>2</sup> /h	25 m <sup>2</sup> /h
	Production	32 m <sup>2</sup> /h	19 m <sup>2</sup> /h
	Quality	24 m <sup>2</sup> /h	14 m <sup>2</sup> /h
Ink Type		Eco Solvent Ink	
Ink Droplet		1.5-21pl variable	
Cleaning		Automatic Cleaning, Anti-Clogging Flash Function & Capping System	
Feed & take up		Automatic Media Feeding (Standard) & Take up System (Optional)	
Environment		Temperature: 20-28°C, Humidity: 40%-60%	
Rip Software		Maintop (Standard)/ FlexiPRINT (Optional)	
Interface		USB 3.0	
Power		AC 110/ 220V, 50/ 60Hz, 1200W	
Size & Weight	Machine	L3130×W710×H1380 mm / 280 KG	
	Packing	L3210×W1000×H740 mm / 400 KG	

Specifications are subject to change without notice.