

# Sublimation Printer

# WJ-7405 & WJ-12605

## Features 特点



#### Epson Official Supplied i3200 Printheads

Two or four heads optional. The speed and quality are guaranteed.

配备Epson原装i3200喷头,速度与品质的保证



## **Heating and Drying System**

Front and middle and rear heating system and front drying fan are standard equipped to help dry the printed material fast.

标配前中后加热系统和前置冷却风扇



#### Anti-collision Function

Anti-collision system is equipped to protect the printhead and carriage all the time.

标配防撞装置,支持中断处续打



### Variable Dot Print Technology

Permitting the printer to provide smooth gradations, exceptional solid colors and optimum image quality in all print modes.

使打印画面的颜色过渡更加自然,实现高质量成像



### Branded parts

Greatly increased the lifetime and stabili ty of the machine. For example, Hiwin guide rail, German Igus drag chain, Italian Megadyne belt.

极大提升设备使用寿命和稳定性

- ★ New look has heavier, larger structure, and wider printing platform 新造型更加厚重大气,更宽的打印平台
- ★ Aluminous carriage girder ensures high accuracy of carriage movement 铝制小车梁,精度有保障
- ★ Dual feeding bar for loading heavy media 双送纸杆,以承受更重的耗材
- ★ Optional infrared heater for drying prints quickly 选配红外加热装置,画面极速烘干
- ★ Integrated temperature controller 一体式温控仪



## **Specification** 参数

Model No.		型号	WJ-740S	WJ-1260S
Printhead		喷头	2/3 Epson i3200	2/3 Epson i3200
Resolution 精度		精度	2400 dpi max	
Media 耗材	Size	尺寸	1.8 meter	3.2 meter
	Types	种类	Heat transfer paper	
Speed 速度	Printing Mode	e 模式	2 print heads	
	Draft	标准	42 m²/h	46 m²/h
	Production	精细	32 m²/h	34 m²/h
	Quality	照片	24 m²/h	26 m²/h
Ink 墨水	Color	色彩	СМҮК	
	Туре	墨水	Sublimation Ink	
Cleaning 清洗		清洗	Automatic Cleaning, Anti-Clogging Flash Function & Capping System	
Heating System 加热		加热	Pre / Middle / Post heating syste & IR heater	
Drying System   干燥		干燥	Equipped	
Feeding & Take up 收放		收放	Standard Equipped	
Rip Software 软件		软件	MainTop (Standard) / FlexiPRINT (Optional)	
Interface 接		接口	USB 3.0	
Power 电源		电源	AC 220V, 50/60Hz	
Size & Weight	Machine	机器	L3100×W780×H1500 mm / 280KG	L4360×W780×H1500 mm / 480KG
	Packing	包装	L3160×W960×H760 mm / 400KG	L4560×W960×H760 mm / 640KG